



 Oil press GmbH & Co. KG	KKF350/10-2
Filter capacity*:	500 l / 130 gal ~24 h**
Number of filter plates:	10 (expandable)
Filter area:	~2,3 m ² / 24.6 ft ²
Chamber volume:	approx. 25 l / 6.6 gal
Voltage – Standard model:	208-230-460 V 3-ph
Voltage – Special version:	220 V 1 ph
Dimension (LxBxH):	1900 x 680 x 1500 mm 74.8 x 26.8 x 59 in
Weight:	approx. 280 kg / 620 lb
Application:	Filtration of crude oil
Scope of delivery:	<ul style="list-style-type: none"> • Chamber filter press equipped with 10 filter plates (from HDPP) & 10 filter cloths (reusable, from PP), pressure switch, pressure gauge, filter cake tub in stainless steel, piping in stainless steel, expansion tank, check valve, pump runtime shutdown, Filling level shutdown, suitable for food-stuff • Eccentric screw pump max. 600 l/h • Candle filter housing (micro filter) with candle filter • Control cabinet (equipped with ON-OFF-DELAY switch) • Electric connection cable (ready to plug-in)

*depending on crude oil, foots content, temperature

**originating from rapeseed oil with 2 % foots content and temperature of 25 °C / 77 °F