

Screening machine for oil & flour



 oil press GmbH & Co. KG	SM600	SM800
Screening capacity for oil:	up to 50 l/h* up to 13 gal/h*	up to 100 l/h* up to 26 gal/h*
Screening capacity for flour:	Control screening: max. 4000 kg/h** :max. 8800 lb/h** Fine screening: max. 500 kg/h** :max. 1100 lb/h**	Control screening: max. 8000 kg/h** :max. 17,600 lb/h** Fine screening: max. 1000 kg/h** :max. 2200 lb/h**
Engine power:	0.85 hp 0.62 kW 230/460 V 60Hz 3 ph	
Dimension (LxBxH):	1070 x 600 x 660 mm 42.12 x 23.62 x 26 in	1270 x 800 x 660 mm 50 x 31.5 x 26 in
Screening area:	0,24 m ² 2.58 ft ²	0,45 m ² 4.84 ft ²
Weight:	approx. 90 kg // 200 lb	approx. 120 kg // 265 lb
Application:	Preliminary filtration of crude oil, flour sifter	
Accessory optional:	Pumping tank, agitator, oil pumps, different screens, several decks possible	
Price:	Furnished upon request	Furnished upon request

*depending on temperature and crude content

**depending on temperature, oil content, fiber content, grain size distribution