

**KERN KRAFT**  
 il press GmbH & Co. KG



	KK Oil prince F Universal
<b>Seed capacity:</b>	up to 15 kg – 33 lb /h*
<b>Engine power:</b>	2,2 kW – 3 hp
<b>Speed (rpm):</b>	15-70 1/min.
<b>Voltage:</b>	230V   50/60 Hz   single-phase
<b>Dimension (LxBxH):</b>	950 x 465 x 510 mm 37.4 x 18.3 x 20.08 in
<b>Weight:</b>	80 kg – 176 lb
<b>Application***:</b>	Almonds, Amaranth**, Apricot kernels, Argan, Avocado seeds, Baobab**, Black cumin, Borage, Brazil nuts (crushed), Camellia, Cashew, Cherry pits, Chia, Coffee beans, Copra/Coconut, Coriander, Corn germ, Cotton seeds, Currant seeds, Elderberry seeds, Evening primrose**, Fenugreek, Gold of Pleasure, Grape seeds**, Hazelnut, Hemp, Jatropha, Jojoba, Lemon seeds**, Linseed, Lupines**, Macadama nuts (crushed), Melon seeds, Milk thistle, Moringa, Mustard, Neem, Niger seed, Peach kernels (peeled), Peanut, Pepper kernels**, Plum kernels (peeled), Pomegranate seeds**, Poppy seed, Prickly pear seed**, Pumpkin seeds, Rapeseed, Raspberry seeds**, Rose hip seeds**, Sacha Inchi (peeled), Safflower, Sesame, Shea (crushed), Soldier fly larvae, Soybeans, Strawberry seeds**, Sunflower seeds, Walnut (crushed), others on request.
<b>Scope of delivery:</b>	<ul style="list-style-type: none"> <li>• <b>Oil press with stainless steel hopper</b> (equipped with standard screw, standard sieve/barrel, standard breaker, standard cover nut, counter nut)</li> <li>• <b>Electrical control cabinet</b> (equipped with 0/1-switch, connection cable, emergency off switch, shockproof plug, frequency converter and speed control)</li> <li>• <b>Heating sleeve 230V</b> incl. shockproof plug</li> <li>• <b>Press nozzle set</b> (Ø 5 - 16mm)</li> <li>• <b>Pressing tools</b> (consisting of 1x nozzle key, 2x hook spanner, 1x stainless oil drain pan)</li> <li>• <b>Food-safe lubricant</b></li> </ul>
<b>Optional equipment:</b>	Special equipment for different seeds
<b>Price:</b>	Prices furnished upon request

\*depending on seed

\*\*short-term, not in continuous operation

\*\*\*depending on seed, additional equipment may be needed